F-THETA LENS

f-160T-10-1030-1080

en | Data sheet | 1.0

- **Telecentric fused silica lens**
- **Wavelength 1030 – 1080 nm**
- **Nominal focal length 160 mm**
- **Max. input beam diameter 10 mm**
- **Maximum working area 75 x 75 mm**



Wavelength	1030 – 1080 nm
Nominal focal length	160 mm
Effective focal length	160.000 mm
Flange focal length	270.000 mm
Working distance	186.000 mm
Max. scan field	75 x 75 mm
Minimum spot size	27.69 µm

Mirror distance m1/m2	13.5 / 24.7 mm
Anti-reflective coating	Standard
Telecentric error	5.1°
Cooling method	Air
Lens material	Fused silica
Mounting thread	M85x1


Information is subject to change without notice.
Product photos are non-binding and may show customized features.


VONJAN TECHNOLOGY GmbH

Neubruch 4
82266 Inning am Ammersee
Germany

Tel.: +49 8143 99681-0
Fax: +49 8143 99681-99
www.vonjan-tech.de

VON.JAN
TECHNOLOGY





F-Theta lens

f-160T-10-1030-1080

Dimensions are given in millimeters and are intended as reference values.
Binding information is available on request.

VONJAN TECHNOLOGY GmbH

Neubruch 4
82266 Inning am Ammersee
Germany

Tel.: +49 8143 99681-0
Fax: +49 8143 99681-99
www.vonjan-tech.de