

# LP1-30L+c

- MOPA Technology
- Large Frequency Range
- High Pulse Energy
- Very Compact Design



## TECHNICAL SPECIFICATIONS:

### LP1-30L+c

Central Wavelength	1064 nm
Nominal Output Power	30 W
Beam Quality	$M^2 < 1.8$
Pulse Frequency Range	1 – 400 kHz
Full Power Frequency	25 – 400 kHz
Maximum Pulse Energy	1.2 mJ @ 25 kHz
Fixed Pulse Width	200 ns <sup>2</sup>
Output Beam Diameter 1/e <sup>2</sup>	6 mm <sup>1</sup>
Power Tuning Range	0 – 100 %
Polarization	Random
Anti Reflective Coating	Yes
Average Power Instability	< 5%
Typical Lifetime Diodes	100.000 h

Fiber Length	2 / 3 / 5 m
Cooling Method	Air
Red Pilot Beam	Optional
Adjustable Pulse Width	No
House-Keeping-Function	24 V
Dimensions W*D*H	234*200*65 mm
Weight	Approx. 4.5 kg
Supply DC Voltage	24 V
Current Consumption	≤ 10 A
Power Consumption (20°C)	≤ 240 W
Operation Temperature	0 – 40 °C
Storage Temperature	-10 – 60 °C

<sup>1</sup> Customized Beam Diameter available from 2,5 to 10,5 mm

<sup>2</sup> Available with Fixed Pulse Width of 20 ns



Manufacturer:

**JPT**