

LP2-30L+c

- **MOPA Technology**
- **Large Frequency Range**
- **High Pulse Energy**
- **Very Compact Design**



TECHNICAL SPECIFICATIONS:

LP2-30L+c

Central Wavelength	1064 nm
Nominal Output Power	30 W
Beam Quality	$M^2 < 1.8$
Pulse Frequency Range	1 – 400 kHz
Full Power Frequency	30 – 400 kHz
Maximum Pulse Energy	1.0 mJ @ 30 kHz
Fixed Pulse Width	200 ns ²
Output Beam Diameter 1/e ²	6 mm ¹
Power Tuning Range	0 – 100 %
Polarization	Random
Anti Reflective Coating	Yes
Average Power Instability	< 5%
Typical Lifetime Diodes	100.000 h

Fiber Length	2 / 3 / 5 m
Cooling Method	Air
Red Pilot Beam	Optional
Adjustable Pulse Width	No
House-Keeping-Function	24 V
Dimensions W*D*H	234*200*65 mm
Weight	Approx. 4.5 kg
Supply DC Voltage	24 V
Current Consumption	≤ 10 A
Power Consumption (20°C)	≤ 240 W
Operation Temperature	0 – 40 °C
Storage Temperature	-10 – 60 °C

¹ Customized Beam Diameter available from 2,5 to 10,5 mm

² Available with Fixed Pulse Width of 20 ns



Manufacturer:

JPT